



ITEM	COPARTNER P/N	LENGTH
1	LS-14100821	1000±30
2	LS-14100822	500±25

WIRE TABLE

P1	P2	
A1,B1,A12,B12	5	GND BLACK
A5	电阻 (5.1KΩ±5%)0402	CC
A4,B4,A9,B9	1	POWER-RED
A6	3	USB2.0 WHITE
A7	2	USB2.0 GREEN
SHELL	SHELL	BRAID

5	PVC	45P PVC BLACK	A/R	9
4	PE	PE NATURAL	A/R	9
3	CONN	USB2.0 MICRO 5PF BLACK INSULATOR SOLDER TYPE	1	SET
2	CONN	USB2.0 C TYPE MALE BLACK INSULATOR SOLDER TYPE 电阻(5.1KΩ±5%)0402	1	SET
1	CABLE	UL2725 2C*28#+1P*28#+AL+D+B JACKET:BLACK OD:3.5mm	A/R	mm
Item	Name	Description	Q'TY	Unit

ELECTRICAL PROPERTIES:  
 1:100% OPEN&SHORT TEST  
 3:CONTACT RESISTANCE: 2 ohm MAX  
 3:INSULATION RESISTANCE:5MEGA ohm  
 (MIN)/300VDC/10ms

THIS DOCUMENT IS THE PROPERTY OF CABLEX AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF Copartner TECHNOLOGY .

金锋电子科技有限公司  
 JINN FENG ELECTRONIC TECH CO.,LTD

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: XXXXX

DIMENSIONS	TOLERANCE	
	INCH	M M
.X	±0.015	±0.30
.XX	±0.010	±0.10
.XXX	±0.005	±0.05

THE 3TH VIEW

DESCRIPTION: USB2.0 CM TO USB2.0 MICRO 5PF L=0.5M/1.0M

CUS. NAME:  
 CUS. P/N:  
 COPARTNER P/N:

DRAW WSC  
 CHECK [Signature]  
 APPROVED JEDI WANG

ENGINEERING NO: LS-14100821-22  
 LOCATION: DONG GUAN DATE: 2015.01.06  
 SCALE: SHEET: 1 OF 1 UNIT: mm REV: B

B	-----	ADD RESISTOR	2015.01.06
A	-----	INITIAL RELEASER	2014.10.08
REVISION	ECN. NO.	REASON	DATE